

M-CL series AC Contactor



M-11CL



M-20CL

APPLICATION

M-CL series AC contactor is suitable for AC 50Hz or 60Hz, voltage up to 660V, current up to 100A electric power system, to switch on & off circuits and AC motors in frequent control. Eleven models M-CL 11, 12, 15, 16, 20, 21, 30, 35, 40, 50 & 60 are available.

TECHNICAL SPECIFICATION

Type	M-11CL	M-12CL	M-18CL	M-20CL
Rated thermal current (A)	20	20	25	32
Rated operating motor (A)	380V	9	12	22
	680V	5	7	9
Power of controllable motor (kW)	330V	4	5.5	7.5
	660V	4	5.5	7.5
Rated frequency of operation cycles / hour	180	180	180	180

Type	M-25CL	M-35CL	M-50CL	M-65CL
Rated thermal current (A)	50	60	80	100
Rated operating motor (A)	380V	30	40	62
	680V	12	17	26
Power of controllable motor (kW)	330V	15	18.5	30
	660V	11	15	30
Rated frequency of operation cycles / hour	180	180	120	120

CN series AC Contactor



CN-11



CN-80

APPLICATION

CN series AC contactor is suitable for AC 50Hz or 60Hz, voltage up to 660V, current up to 60A circuit, five models of CN-11, 16, 18, 25, 35 are available. They are able to assemble building block, auxiliary contactor group, thermal relay & accessories etc, to form multifunction series products.

TECHNICAL SPECIFICATION

Type	CN-11	CN-16	CN-18	CN-25
Rated insulated voltage (V)	660V	660V	660V	660V
Rated heat current (A)	25	25	35	50
Capacity of 3 phase squirrel-cage motor AC3 (kW)	220V	3	4	5.5
	380V	4	5.5	9
	350V	5.5	7.5	11

Type	CN-35	CN-50	CN-65	CN-80
Rated insulated voltage (V)	660V	660V	660V	660V
Rated heat current (A)	60	80	90	110
Capacity of 3 phase squirrel-cage motor AC3 (kW)	220V	11	18	30
	380V	18.5	22	45
	350V	22	25	40