

TDGC2 TSGC2 Contact Voltage Regulator

APPLICATION

The product is characterised of non-lack fidelity in waves, portable size, light weight, high efficiency, convenience to use, reliability in non-vent. It is widely used in chemical, metallurgical meter and instrument, machine-building and light industries, for voltage regulating, air conditioning, air conditioning speed, light and rate regulating, it is an ideal AC regulating power supply.



TDGC2



TSGC2

MAIN TECHNICAL PARAMETER

Type	Rated capacity (kVA)	No. of phase	Nominal frequency (Hz)	Rated input voltage	Rated output voltage(V)	Rated output voltage(V)
TDGC2-0.2	0.2	1	50	220	0-250	0.8
TDGC2-0.5	0.5					2
TDGC2-1	1					4
TDGC2-2	2					8
TDGC2-3	3					12
TDGC2-4	4					16
TDGC2-5	5					20
TDGC2-7	7					28
TDGC2-10	10					40
TDGC2-15	15					80
TDGC2-20	20					80
TDGC2-30	30					120
TSGC2-3	3	3	50	380	0-430	4
TSGC2-6	6					8
TSGC2-9	9					12
TSGC2-12	12					16
TSGC2-15	15					20
TSGC2-20	20					27
TSGC2-30	30					40