

E27/E40 Porcelain Lampholder



EF519E



EF519K



EF519T



EF519E-1



EF519E-2



EF519E-1W



EF519W



EF519A φ 4



EF519A-2.2XM3



EF519C



EF519D



EF519S



EF519T-1



EF526F



EF526E



EF526J



EF526E-1



EF526G



EF526T



EF526X

Magnetic Ballast/Electronic Ballast

SPECIFICATIONS

1. Electronic Ballast

1) Series:

- a. Electronic Ballast for T5 type fluorescent lighting fixture and lamps.
- b. Electronic Ballast for T8 type fluorescent lighting fixture and lamps.
- c. Electronic Ballast for T12 type fluorescent lighting fixture and lamps.

2) Power: suitable for 12W-80W, 1-4pcs lamps.

3) Voltage/Frequency: 110-130V,220-240V,120V, 277V,347V, 120-277V, 277-347V ; 50/60Hz.

4) Material: copper wire.

5) Certification: CE,CQC, UL, CSA

2. Magnetic ballast

1) Series:

- a. Magnetic ballast for T5, T8, T12 type lighting fixture and lamps.
- b. Magnetic ballast for Sodium lamps.
- c. Magnetic ballast for metal halide lamps.
- d. Magnetic ballast for mercury lamps.
- e. Magnetic ballast for stage lamps.

2) Power: suitable for 17W-2000W.

3) Voltage/Frequency: 110-130V,220-240V,120V, 277V, 347V, 120-277V, 277-347V; 50/60Hz.

4) Material: copper wire or aluminum wire.

5) Certification: CE,CQC, UL, CSA..

