

### ID series Earth Leakage Circuit Breaker

#### APPLICATION

They have a residual current operated electromechanical release which operates without any auxiliary source of supply to open a circuit automatically in the case of an earth leakage fault between phase and earth greater than or equal to a threshold of 10mA, 30mA, 100mA, 300mA or 500mA.

#### SPECIFICATION



ID-2P



IDN-2P



ID-4P



IDN-4P

Type	Width in mod of 9mm	Rat (A)	Sens (mA) 50Hz	Cat. No CEE27ID 240V	BS4293 RCCB 240V				
2P	4	16	10		23081				
			10	23008	23082				
			30	23009	23083				
		40	4	30	300	23011	23086		
					30	23014	23088		
					100	23015			
				63	4	30	300	23016	23090
							500	23017	
							30	23018	23093
		80	4	30	100		23094		
					300	23021	23095		
				100	4	500	23022		
30							23097		
100	4			30	100		23098		
					300	23030	23100		
100	4			500	30		23101		
					100		23102		
					300	23034	23103		
					500	23035	23116		

Type	Width in mod of 9mm	Rat (A)	Sens (mA) 50Hz	Cat. No CEE27ID 415V	BS4293 RCCB 415V				
4P	8	25	30	23038	23118				
			300	23040	23121				
			40	23042	23123				
		40	8	40	100	15176			
					300	23045	23125		
					300	23062			
				63	8	500	500	23046	
							500	23063	
							30	23047	23128
		80	8	63	10	15177	23129		
					300	23049	23120		
					300	23066	23146		
100	8			500	500	23067			
					300	23054			
					300	23069			
100	8			100	300	23056			
					300	23059			
					300	23059			