

Lotus/Globe Energy Saving Lamps

FEATURE

It introduces the latest wires and technology, it is anti-jamming, it is made from non-flammable PBT plastic with ultraviolet resistance, it is characterized by its attractive appearance, gentle light rays and long service life.

APPLICATION

It is suitable for factory, supermarket, plaza etc large areas lighting places.

SPECIFICATIONS

CE & ROHS, ISO9001

1. Voltage/Frequency: 110V-130V / 220V-240V, 50Hz-60Hz;
2. Power: 3W ~ 150W;
3. Base: E27 / E22 / E14 / E17 / E40 / B22;
4. Life: 5000~10000 hrs;
5. Color temperature: 2700k - 7000k;
6. Tube inside powder: Halogen / tri-color / mixed powder;
7. Packaging: Standard Export Carton.



YPZ28-L



YPZ5-G



YPZ13-G



YPZ20-G

Type	Voltage (V)	Watt (W)	Luminous Flux (lm)	Color temp (k)	Tubular (mm)	Size (mm)	Life (hrs)	Base
YPZ20-L	110-130 220-240	20	1260	2700 3200 4500 5000 6400 6500 7000	φ 12	170	5000-10000	E14 E17 E27 E22 B22 E40
YPZ22-L		22	1390		φ 9	138		
YPZ24-L		24	1500		φ 9	138		
YPZ26-L		26	1640		φ 12	180		
YPZ28-L		28	1760		φ 12	185		
YPZ32-L		32	2020		φ 12	180		
YPZ36-L		36	2260		φ 14	205		
YPZ40-L		40	2520		φ 14	215		
YPZ45-L		45	2830		φ 14	225		
YPZ55-L		55	3460		φ 14	235		
YPZ65-L		65	4090		φ 17	310		
YPZ85-L		85	5350		φ 17	330		
YPZ105-L		105	5780		φ 17	282		
YPZ120-L		120	6600		φ 17	282		
YPZ150-L	150	8250	φ 17	350				
YPZ3-G	110-130 220-240	3	120	2700 3200 4500 5000 6400 6500 7000	φ 9 2U	107	5000-10000	E14 E17 E27 E22 B22 E40
YPZ5-G		5	200		φ 9 2U	107		
YPZ9-G		9	360		φ 9 3U	124		
YPZ11-G		11	440		/Spiral	124		
YPZ13-G		13	504		φ 9 3U	158		
YPZ15-G		15	600		φ 9 3U	158		
YPZ20-G		20	720		φ 12 3U	160		