


Time Relay

TECHNICAL SPECIFICATION

Classification	Timer	Timer	Timer	Timer
Type	SUL181h	TR-72	TB-35/TB-38	GST8
Contact capacity	AC220V 10A	AC220V 10A	AC220V 10A	AC220V 16A
Full timing range	24h	24h	24h	7m
Contact resistance	≤50mΩ	≤50mΩ	≤50mΩ	≤50mΩ
Insulation resistance	≥100mΩ	≥100mΩ	≥100mΩ	≥100mΩ
Coll voltage	220V AC	110, 230V AC	110, 230, 240V AC	220V AC
Life	Mechanical	10 ⁵ times	10 ⁵ times	10 ⁵ times
	Electrical	10 ⁷ times	10 ⁷ times	10 ⁷ times
Operating temperature	-40°C ~ +55°C			
Storage battery (working reserve)	Time 150h		---	---
Minimum setting unit	30 minutes	15 minutes	15 minutes	0.5 minutes
Set up times	30m/per times 48times	15m/per times 96times	15m/per times 96times	1M, 1.5M, 2M, 2.5M, 3M, 3.5M, 4.5M, 5M, 5.5M, 6M, 6.5M, 7M
Remarks	---	---	TB-35 without iron box TB-38 with iron box	---



SUL 181h



TR-72



TB-35/TB-38



GST8

DIMENSIONS (mm)

